

## Ease of Use

- Windows XP Interface
- Large, Sunlight-Visible Display
- Resistive (Finger) Touch Screen
- USB Data Transfer

## **Updated Software**

- Customizable Display
- Real-Time Data and Diagnostics
- Easy to Set-up and Operate
- Autonomous Control of Air Pressure, Vacuum, and Hydraulic Temperature

## New Technology

- State of the Art Computer
- Modular, Updateable, Electronics
- Multiple Integrated Processors

## Durability

- Monitor Sealed to IP68, NEMA 6P
- All Solid-State Electronics, No Moving Parts
- Most Components Rated for –40°C to 85°C (-40°F to 185°F)

SeedPro 3	cedPro 360 - DEFAULTS File  Plant Options  Diagnostics  Settings Message Center Help										
Current Range: 1 Next Count: 36			Next Range: 2 Prev. Time: 0			Packet Range: 4 Prev. Dist. (in): 0.0			Start Cycle		
	1	2	3	4	5	6	7	8	Row Unit	K	
	0	0	0	0	0	0	0	0	Current Count	₩	
	0	0	0	0	0	0	0	0	Current Doubles		
	0	0	0	0	0	0	0	0	Current Skips	++	
									Prev. Count		
Seed Count										e-STOP	



